



## TECHNICAL SPECIFICATION SHEET



### 150MM AXIAL FAN WITH TIMER AND SHUTTERS

426568

**Axial extract fan with backdraught shutter and electronic overrun timer adjustable from 1 minute to 25 minutes, the factory setting is 15 minutes. Suitable for panel mounting or wall/window mounting using the appropriate accessory kit.**

**Key features:**

- Suitable for panel, wall or window mounting.
- All non pull-cord variants can be ceiling mounted
- High quality ABS mouldings with external gloss finish
- Quiet Operation
- Reversible grommet for surface of flush mounting.

**Technical specification:**

- Meets the requirements of Building Regulation Document F.
- IP44 rated, BEAB Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives.
- Double Insulated, class II motor fitted with thermal protection
- Hole Diameters: Window 160mm, Wall 170mm
- Airflow: Panel Mount 245m<sup>3</sup>/hr, Window/Wall 220m<sup>3</sup>/hr

**Product range details:**

- Rated Voltage 220-240v-50Hz
- Rated Wattage 25W

**Accessories:**

- Window Kit
- Wall Kit
- External wall grille
- External gravity wall grille
- Ducting

**Dimensions:**

H225 x W218 x D119mm